

Logiciel

Graphique

Cutycapt

Cutycapt est une application qui fonctionne en ligne de commande, il permet de réaliser des copies d'écran de site internet.

Pour l'installer:

```
sudo apt-get install cutycapt
```

Pour l'utiliser:

```
cutycapt --url=http://google.fr --out=google_fr.png
```

L'ensemble des commandes:

<code>--help</code>	Print this help page and exit
<code>--url=<url></code> (http:... file:... ...)	The URL to capture
<code>--out=<path></code> (.png pdf ps svg jpeg ...)	The target file
<code>--out-format=<f></code> heuristic	Like extension in --out, overrides
<code>--min-width=<int></code> (default: 800)	Minimal width for the image
<code>--min-height=<int></code> (default: 600)	Minimal height for the image
<code>--max-wait=<ms></code> 90000, inf: 0)	Don't wait more than (default:
<code>--delay=<ms></code> (default: 0)	After successful load, wait
<code>--user-style-path=<path></code> if any	Location of user style sheet file,
<code>--user-style-string=<css></code>	User style rules specified as text
<code>--header=<name>:<value></code> can't be set	request header; repeatable; some
<code>--method=<get post put></code> (default: get)	Specifies the request method
<code>--body-string=<string></code> none)	Unencoded request body (default:
<code>--body-base64=<base64></code> (default: none)	Base64-encoded request body
<code>--app-name=<name></code> is none	appName used in User-Agent; default
<code>--app-version=<version></code> is none	appVers used in User-Agent; default

<code>--user-agent=<string></code> would set	Override the User-Agent header Qt
<code>--javascript=<on off></code>	JavaScript execution (default: on)
<code>--java=<on off></code>	Java execution (default: unknown)
<code>--plugins=<on off></code>	Plugin execution (default: unknown)
<code>--private-browsing=<on off></code>	Private browsing (default: unknown)
<code>--auto-load-images=<on off></code> on)	Automatic image loading (default: on)
<code>--js-can-open-windows=<on off></code> unknown)	Script can open windows? (default: unknown)
<code>--js-can-access-clipboard=<on off></code> unknown)	Script clipboard privs (default: unknown)
<code>--print-backgrounds=<on off></code> (default: off)	Backgrounds in PDF/PS output
<code>--zoom-factor=<float></code> zooming)	Page zoom factor (default: no zooming)
<code>--zoom-text-only=<on off></code> (default: off)	Whether to zoom only the text
<code>--http-proxy=<url></code> (default: none)	Address for HTTP proxy server

From: <http://poste2travail.free.fr/dokuwiki/> - **Poste2Travail**

Permanent link: <http://poste2travail.free.fr/dokuwiki/doku.php?id=os:linux:logiciel> 

Last update: **2020/08/10 23:07**